## REVISIONS ISSUE 26/2019 DATE DAT SEWER LINE ABOVE WATER LINE ABOVE WATER LINE SEWER LINE SEWER LINE WATER LINE щ MORE THAN 12 INCHES BUT LESS THAN 18 INCHES SEPT ADDED MORE THAN 12 INCHES MINIMUM 18 INCHES, SANITARY PARALLEL DISTANCE REQUIREMENT **EMBER** Ł Β 0 B 4 PROVIDE CRADLE OF CONCRETE OR CRUSHER RUN STONE (SEE TRENCH SECTION DETAIL THIS SHEET) FOR WATER LINE AND SEWER LINE FOR ENTIRE LENGTH OF PIPE EACH SIDE OF CROSSING. SEWER/WATER WATER LINE AND SEWER LINE SHALL BE ONE FULL LENGTH CENTERED AT CROSSING, WHEN POSSIBLE. SLEEVE SEWER LINE WITH STEEL CASING FOR ENTIRE LENGTH OF PIPE (EACH SIDE OF CROSSING). COMMENTS WHEN BOTH WATER LINE AND SEWER LINE ARE NEW, SLEEVE SEWER LINE WITH STEEL CASING FOR FULL LENGTH OF PIPE WHEN ONE LINE IS EXISTING, SLEEVE PIPE BEING INSTALLED WITH STEEL AT CROSSING. WATER LINE AND SEWER LINE SHALL BE ONE FULL LENGTH CENTERED AT CROSSING, WHEN POSSIBLE. CASING FOR ONE FULL LENGTH OF PIPE. 2018 -0R--N. T.S. CROSSING EVL SEWER TOWN & Ņ ENG DETAI DEPT. VILLAGE S-08 유

**ELLICOTTVILLE** 

## OTHER NOTES:

WAIER

LINE-SEWER

CROSSING PROVISIONS

SCHEMATIC

- WHEN INSTALLED PARALLEL WITH ONE ANOTHER, WATER AND SEWER LINES SHALL BE A MINIMUM OF 10 FT APART.

  OTHER UTILITIES SHALL BE A MINIMUM OF 5 FT APART WHEN INSTALLED IN PARALLEL WITH WATER OR SEWER LINES.